


Cestino cilindrico SAFE 15L

Codice articolo	330501	Minimo d'ordine	1 Pezzo
Colore	Nero	EAN minimo d'ordine	4005546988504
Confezionamento	1 pezzo	Peso confezione (lordo)	2015 G
EAN	4005546988504	Paese d'origine	DE



Loghi e premi



Descrizione prodotto

- Cestino cilindrico con coperchio autoestinguente per la prevenzione degli incendi
- Il coperchio autoestinguente blocca l'apporto di ossigeno all'interno, di conseguenza le fiamme si spengono
- Certificato TÜV
- In acciaio verniciato a polveri epossidiche, antigraffio
- Capacità: 15 litri

Caratteristiche prodotto

Altezza esterna (mm)	357
Ø esterno (mm)	260
Quantità (per)	15 l

330501_PDS_DURABLE_it_IT.pdf | 2026-08-03 12:58

1/2

DURABLE Hunke & Jochheim GmbH & Co. KG
Westfalenstraße 77 - 79 · 58636 Iserlohn · Germany
Phone +49 (0) 2371 662 0 · Fax +49 (0) 2371 662 221
Mail durable@durable.de | durable.de

The statements contained herein are for informational purposes only and are true and accurate to the best of our scientific and technical knowledge. This information does not constitute a guarantee or warranty, express or implied, nor does it establish a legally valid contractual relationship. It is the customer's responsibility to determine the suitability of this product for the customer's intended use. DURABLE does not assume any liability for the customer's use of this product or the information contained herein.




Cestino cilindrico SAFE 15L

Marchio	DURABLE
Forma	Rotonda
Tipologia di coperchio	Coperchio autoestinguente rimovibile
Cestino interno rimovibile	No
Anello ferma sacco	no
Autoestinguente	Sì
Impilabile	No
Area di utilizzo	Aree interne


General test information on waste bins SAFE und SAFE+

Abstract of the GS test specification 2 PfG 1198/10.15

Article 3305 / 3306 / 3307



Article 3325 / 3326 / 3327



Test specification abstract (2 PfG 1198/10.15)

The GS test of TÜV Rheinland regarding "self-extinguishing" is carried out, in excerpt, according to the following technical test specifications.

(a suspended bag is not provided for according to the GS test specification)

Testing room:	draught-free 18° C - 28° C room temperature
Audit:	Extinguishing the burning waste bin within 1 minute 1 x full waste bin 1 x 1/2 full waste bin 1 x 1/3full waste bin
Warming up:	heat the bottom of the waste bin not above 90° C.

DURABLE

Hunke & Jochheim GmbH & Co. KG
Westfalenstraße 77-79
D-58636 Iserlohn

Telefon +49 (0) 2371 / 662 – 0
Telefax +49 (0) 2371 / 662 – 221
Internet www.durable.de
E-Mail durable@ durable.de

The statements contained herein are for informational purposes only and are true and accurate to the best of our scientific and technical knowledge. This information does not constitute a guarantee or warranty, express or implied, nor does it establish a legally valid contractual relationship. It is the customer's responsibility to determine the suitability of this product for the customer's intended use. DURABLE does not assume any liability for the customer's use of this product or the information contained herein.

